SOFAR 15-25KTLX-G3P

15 / 17 / 20 / 23 / 25 kW

Three-phase string inverter



Flexible power adaptation

- Compatible with 182 & 210 high power PV modules
- Low start-up and wide MPPT voltage range

Robust performance

- Prolonged AC overload compatibility (110%)
- Type II SPD for both DC and AC sides

Smart O&M

- Smart string level monitoring
- Remote upgrade via SofarCloud

www.sofarsolar.com

© As of November 2025, SOFARSOLAR Co.,Ltd. The depiction of colors and shape of the product may differ from the original. SOFAR reserves the right to make changes or improvements to the products without prior notice. Ordering information is valid for specialist retailers. All brands or logos are trademarks or registered trademarks of their respective owners. All rights, technical modifications, and errors reserved.

Model	SOFAR 15KTLX-G3P	SOFAR 17KTLX-G3P	SOFAR 20KTLX2-G3P	SOFAR 23KTLX-G3P	SOFAR 25KTLX-G3P
Input (DC)					
Max. input voltage	1100V				
Rated input voltage	620V				
Start-up voltage	180V				
MPPT operating voltage range	160-1000V				
Number of MPP trackers	2				
Number of DC inputs	1/2		2/2		
Max. input MPPT current	20A/32A		40A/32A		
Max. input short circuit current	25A/40A		50A/40A		
Output (AC)					
Rated output power	15000W	17000W	20000W	23000W	25000W
Max. apparent power	16500VA	18700VA	22000VA	25300VA	27500VA
Max. output current	25.1A	28.5A	33.5A	38.5A	41.8A
Rated output voltage	3/N/PE, 220/380Vac, 230/400Vac, 240/415Vac				
Output voltage range	310-480Vac				
Rated output frequency	50/60Hz				
Output frequency range	45-55Hz / 55-65Hz				
Active power adjustable range	0-100%				
THDi	< 3%				
Power factor	0.8 leading – 0.8 lagging				
Efficiency					
Max. efficiency	≥ 98.6%				
European efficiency	≥ 98.1%				
Protection					
DC reverse polarity protection	Yes				
Anti-islanding protection	Yes				
Leakage current protection	Yes				
Ground fault monitoring	Yes				
PV-array string fault monitoring	Yes				
DC switch	Yes				
SPD	PV: type II, AC: type II				
General Data					
Ambient temperature range	-30˚C ~ +60˚C				
Self-consumption at night	< 1 W				
Topology	Transformerless				
Degree of protection	IP66				
Allowable relative humidity range	0-100 %				
Max. operating altitude	4000m (>2000m derating)				
Cooling	Smart air cooling				
Dimension (W×H×D)	491×412×188 mm				
Weight	19 kg	20 kg	20.5 kg		
Display	LCD & Bluetooth +APP				
Communication	RS485 / Wi-Fi				
Standard	IEC/EN 62109-1/2, IEC/EN 61000-6-1/2/3/4, IEC 62116, IEC 61727, IEC 61683, IEC 60068-2-1/2/14/30, VDE-AR-N 4105, VDE V 0126-1-1, EN 50549-1/10				

*All specifications are subject to change without notice.